

PRO® 406

Double Coated Polyester Tape



Technical Data Sheet

Pro® 406 is a 3.9 mil double coated polyester tape.

Features & Benefits:

Bonds well to most substrates at room temperature

High tack

High peel strength

Designed to bond well to: foams, felt, sponge, cork, abrasive materials and gasket materials

Technical Data

- ⇒ Product Type: Double coated polyester tape with rubber adhesive
- ⇒ Adhesive: Rubber
- ⇒ Carrier: 60# Polycoated lay-flat silicone treated release liner
- ⇒ Liner Side Adhesive Thickness: 1.7 mils
- ⇒ Exposed Side Adhesive Thickness: 1.7 mils
- ⇒ Carrier Thickness: 0.5 mils
- ⇒ Total Thickness: 3.9 mils
- ⇒ Elongation: 350%
- ⇒ Tensile strength: 10 lbs. per inch
- ⇒ Peel exposed side: 130 oz./in, high
- ⇒ Peel liner side: 100 oz./in, high
- ⇒ Shear exposed side: 24+ hours
- ⇒ Shear liner side: 24+ hours
- ⇒ Application Temperature: 41°F to 104°F

Application:

Pro® 406 is a general purpose rubber based adhesive tape designed for bonding to a variety of polyurethane and polyethylene foams, felt, rubber, sponge, cork, abrasive materials and gasket materials.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.