

PRO® SPLICE 50 PREMIUM VINYL TAPE

Technical Data Sheet


Pro® Splice 50 is a premium vinyl tape designed for safety marking and dance floor splicing.

Features & Benefits:

- Highly conformable to all surfaces
- Abrasion resistant
- Used for color coding
- Used to splice dance floors
- Satisfies all O.S.H.A. marking requirements

Technical Data

- ⇒ Backing: PVC
- ⇒ Adhesive: Natural Rubber Resin
- ⇒ Total Thickness: 6 mils
- ⇒ Tensile strength: 18 lbs. per inch
- ⇒ Adhesion to steel: 12.6 oz./in
- ⇒ Elongation: 180%
- ⇒ Temperature Resistance 176°F
- ⇒ Government Specification: PPP-T-66D, Type 1
- ⇒ Colors: White, Black, Blue, Clear, Grey, Red, Yellow, Green, Orange, Brown, Purple



Application:

- Safety Marking
- Dance Floor Splicing

ISO 9001
Certified



WARNING: This product can expose you to chemicals including Diisononyl phthalate (DINP), which is known to the State of California to cause cancer and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.